

MADE IN ITALY

CUPEX GEL



AIR CONDITIONING



EUROCLASSE B s2 dB - CUPEX GEL 1/4x1 IGQ



www.zetaesse.it

CUPEX GEL



AIR CONDITIONING



The best pipe for air conditioning systems

The new appliances that operate with coolant type R 410A and R 32 reach higher temperatures than the previous models. That requires the pipes to have a special covering to stand up to these performances.

FEINROHREN SUPERGREEN FIVE STARS COPPER PIPE

- Alloy: Cu-DHP (Cu 99,90% min min, P: 0,015-0,040%) according to UNI EN 12449.
- Dimensions, tolerances and cleaning according to EN 12735-1, certified IGQ P112.
- Carbon residuals <0,05 mg/dm².
- Guarantee: 30 year against corrosion.

FIELDS OF USE

- Air conditioning and refrigeration systems (R410A, R32...).
- Heat pumps.

ZETACELL COATING

- External: LD-PE film.
- Internal: CROSS-LINKED CLOSED CELLS POLYETHYLENE foam according to EN 14313.
- Coating thickness according to EN ISO 15758/2016, D.L.10/91, DPR 412/93.
- CFC and HCFC free (Reg. CEE/UE2037/2000).
- Steam diffusion resistance $\mu > 9'000$ (EN 13469).
- Operating temperature: -80 +120 °C.
- Reaction to fire: Euroclass B s2 d0 according to EN 13501-1 CE.
- Marking: ZETAESSE EUROCLASSE B s2 d0 EN 13501-1 CE CUPEX GEL 1/4X1 EN 12735-1 IGQ P112 GAS R410A R32 TRIM. ANNO L.



Copper pipe ø OD		Available thickness	Insulation thickness	Max working pressure	Nominal weight copper pipe
Inches	mm				
1/4	6,35	0,8/1	9,0	134	150
3/8	9,52	0,8/1	9,0	89	238
1/2	12,70	0,8/1	9,0	72	327
5/8	15,87	1	11	57	416
3/4	19,10	1	11	52	505
7/8	22,22	1	11	42	594



ZETAESSE SPA

Via Vicenza 45, - 31050 VEDELAGO (Tv) - Italy - T +39 (0)423700711 - F +39 (0)423401177 - info@zetaesse.it - www.zetaesse.it